XGSZCNFAC

Electronic tag, Radio frequency identification XG, set of badges for setup of the standalone reader



Main

Range of product	Telemecanique Radio frequency identification XG
Product or component type	Electronic tag
RFID electronic tag name	XGSZ
RFID frequency	13.56 MHz
Design	ISO badge
Associated smart antenna	XGCS491
Outer dimension	54 x 85.5 x 1 mm
Quantity per set	Set of 1
IP degree of protection	IP65

Complementary

Memory type	EEPROM	
Memory operation	Read	
Number of read cycles	Unlimited	
Number of write cycles	- at -2550 °C	
Data retention time	10 year(s)	
Material	PVC (polyvinyl chloride)	
Net weight	0.03 kg	

Environment

Standards	ISO 14443	
Ambient air temperature for operation	-2550 °C	
Ambient air temperature for storage	-4055 °C	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	1.5 cm	
Package 1 Width	8.5 cm	
Package 1 Length	11.0 cm	
Package 1 Weight	25.0 g	
Unit Type of Package 2	S01	
Number of Units in Package 2	64	
Package 2 Height	15.0 cm	
Package 2 Width	15.0 cm	
Package 2 Length	40.0 cm	
Package 2 Weight	1.781 kg	

Offer Sustainability

REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₽¥Yes
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov